



EASY & EASY-Q

DIGITALENDSTUFEN

FEATURES

Die Digitalendstufen der „EASY“ Generation zeichnen sich durch ihre enorme Leistung bei geringem Gewicht aus. Das verbaute DSP besticht durch seine einfache Bedienung und kann mittels dem großen Touchscreen in der Front auch im Betrieb schnell und unkompliziert gesteuert werden. Über die mitgelieferte Software können Presets hochgeladen, erstellt oder gespeichert werden. Die Verbindung zum PC kann über USB oder im Netzwerk erfolgen.

- Digitale Endstufe mit DSP
- USB- und netzwerkfähig
- 4-polige Speakerausgänge
- großes Touchscreen
- Temperaturgesteuerte Lüfter
- Kompaktes 2HE Gehäuse

SPECIFICATION

2 Kanal Model	EASY-6	EASY-9	EASY-12	EASY-15	EASY-18
4 Kanal Model	EASY-6Q	EASY-9Q	EASY-12Q	EASY-15Q	EASY-18Q
Leistung 8 Ohm	600 Watt	900 Watt	1250 Watt	1500 Watt	1800 Watt
Leistung 4 Ohm	1200 Watt	1800 Watt	2500 Watt	3000 Watt	3600 Watt
THD	< 0.03%				
frequency response (10 dB output power)	20 Hz - 20 kHz, ± 0.15 dB / -3 dB points: 5 Hz and 50 kHz				
input sensitivity	0.775V / 1V / 1.4V				
damping factor	> 400 @ 8 Ω				
hum&noise	102dB				
input impedance	10 k Ω unbalanced 20 k Ω balanced				
connectors	input: 2 channels of XLR F & XLR M; 4 channels of XLR F output: speakon				
cooling	front-to-rear airflow, temperature controlled fans				
protections	short circuit, open circuit, overheat, radio-frequency, ultrahigh or ultralow frequency protection				
Power requirement	AC 220 V ($\pm 10\%$) 50-60 Hz				
Dimensions(mm)	88x483x425				
Net weight	12 kg (4 Kanal Version) / 11 kg (2 Kanal Version)				